

### LED DRIVER



Drei LED Driver mit unterschiedlichen Ausgangsspannungen

**Kurzschlusschutz**

**Überlastschutz**

**Temperaturabschaltung**

Three LED drivers with different output voltages

**Short circuit protection**

**Overload protection**

**Thermal protection**

Tres controladores LED con diferentes tensiones de salida

**Protección contra cortocircuitos**

**Protección contra sobrecarga**

**Protección térmica**

<b>Best.-Nr.:</b> <b>Order No.:</b> <b>No ped.:</b>	<b>LMV 12W5</b>	<b>LMV 12W12</b>	<b>LMV 12W24</b>
Teillastbereich Shared load operation Funcionamiento con carga parcial	3-12W		
Nennspannung Rated voltage Tensión nominal	220-240V~		
Sekundärspannung Secondary voltage Tensión secundaria	5VDC	12VDC	24VDC
Netzfrequenz Mains frequency Frecuencia de red	50-60Hz		
Kurzschlusschutz Short circuit protection Protección contra cortocircuito	ja yes si		
Überlastschutz Overload protection Protección contra sobrecarga	ja yes si		
Temperaturabschaltung Thermal protection Protección térmica	ja yes si		
Schutzklasse Protection class Grado de protección	II		
Abmessungen L x B x H Measurements l x w x h Dimensiones L x A x H	85 x 40 x 22mm		
Prüf-/ Kennzeichen Approbations Homologaciones	  		

