

LED DRIVER



Konstantstromquelle

- Konstanter Ausgangsstrom 350mA

Teillastbereich

- Für 1-8 power LED

Kurzschlusschutz

Temperaturabschaltung

Überlastschutz

Constant current source

- Constant output current 350mA

Shared load operation

- For 1-8 power LED

Short circuit protection

Thermal protection

Overload protection

Fuente de corriente constante

- Corriente de salida constante de 350mA




Funcionamiento con carga parcial

- Para 1-8 power LED

Protección contra cortocircuitos

Protección térmica

Protección contra sobrecarga

Best.-Nr.: Order No.: No ped.:	LMVC8A	LRVC9A
Teillastbereich Shared load operation Funcionamiento con carga parcial	1-8 1W High power LED	1-9 1W High power LED
Sekundärspannung Secondary voltage Tensión secundaria	3-24VDC 350mA	3-27VDC 350mA
Nennspannung Rated voltage Tensión nominal	220-240V~	
Netzfrequenz Mains frequency Frecuencia de red	50-60Hz	
Kurzschlussschutz Short circuit protection Protección contra cortocircuito	ja yes si	
Überlastschutz Overload protection Protección contra sobrecarga	ja yes si	
Temperaturabschaltung Thermal protection Protección térmica	ja yes si	
Schutzklasse Protection class Grado de protección	II	
Abmessungen L x B x H Measurements l x w x h Dimensiones L x A x H	85 x 40 x 22mm	54mmØ x 22mm
Prüf-/ Kennzeichen Approbations Homologaciones	  	

LED Driver

