

LED Driver als Konstantstromquelle



Konstantstromquelle

- Konstanter Ausgangsstrom 350mA, 700mA

Teillastbereich

- Für 1-3High power LED

Kurzschlusschutz

Überlastschutz

Constant current source

- Constant output current 350mA , 700mA

Shared load operation

- For 1-3High power LED

Short circuit protection

Overload protection

Fuente de corriente constante

- Corriente de salida constante de 350mA, 700mA

Funcionamiento con carga parcial

- Para 1-3High power LED

Protección contra cortocircuitos

Protección contra sobrecarga

Best.-Nr.: Order No.: No ped.:	LSVC3A UNI	LSVC3B UNI
Teillastbereich Shared load operation Funcionamiento con carga parcial	1-3 High power LED in Serie 1-3 High power LED in series 1-3 High power LED en serie	
Sekundärspannung Secondary voltage Tensión secundaria	3-9VDC	3-5VDC
Konstantstrom	350mA	700mA
Nennspannung Rated voltage Tensión nominal	100-240V~	
Netzfrequenz Mains frequency Frecuencia de red	50-60Hz	
Kurzschlusschutz Short circuit protection Protección contra cortocircuito	ja yes si	
Überlastschutz Overload protection Protección contra sobrecarga	ja yes si	
Schutzklasse Protection class Grado de protección	II	
Abmessungenn L x B x H Measurements l x w x h Dimensiones L x A x H	48 x 39 x 20mm	
Prüf-/ Kennzeichen Approbations Homologaciones	KEMA CE	

