


Ruedas con neumático (velocidad <25 Km./h.).

Wheels with tyre (speed <25 Km./h.).



01



02



03



04



05

CONJUNTOS CON NEUMÁTICOS DE TRACCIÓN / SETS WITH TRACTION TYRES.

Ø	COD	Tread Pattern	00	Tread Profile	Flange	Bolt	Nut	Washer	Kg	Pressure		Kg		
										BAR	P.S.I.			
Ø8	-	3.50 - 8" 4PR	01	2.50A-8"	04/52x70x11-H	-2,2	101	395	185	3	44	4,2		
	-	4.00 - 8" 2PR							155	1,5	22	5		
	-	16x6.5 - 8" 4PR							225	2,8	41	7		
10"	-	4.00 - 10" 2PR		3.50x10"	04/58.5x98x15.5-G16	-8	154	416	280	1,9	28	7		
	-	5.00 - 10" 2PR							114	463	170	1	15	4
	-	5.00 - 10" 4PR							140	512	255	2,3	34	7
12"	-	4.00 - 12" 4PR		3.00Bx12"	04/58.5x98x15.5-E16	0	115	533	300	2,75	39	8		
	-	5.00 - 12" 2PR							145	580	255	1,25	18	10,2
	-	5.00 - 12" 4PR							129	573	255	2	29	10,5
	-	6.50/80 - 12" 4PR							165	604	490	2,4	35	10,2
15"	-	7.00 - 12" 6PR		4.25x12"	05/94x140x18.5-E1	0	187	667	690	2,5		16		
	-	5.00 - 15" 4PR							129	661	430	2,2	33	15
	-	6.5/80 - 15" 6PR							163	685	585	2,4	35	17
15,3"	2740	10.0/75 - 15,3" 10PR		05	9.00x15,3"	06/161x205x21.5-E2	-15	264	780	1090	3,9	56	40	
	12850	10.0/75 - 15,3" 10PR								1525	4	58	37	
	12858	10.0/75 - 15,3" 10PR	290							867	1360	3,4	50	40
	13980	11.5/80 - 15,3" 10PR									2430	4,75	69	48
	12807	11.5/80 - 15,3" 10PR												
15,5"	12051	400/60 - 15,5" TL 14PR	04	13.00x15,5"	06/161x205x21.5-A2	-15	405	875	2745	3,5	51	63		
	16"	11697	6.00 - 16" 6PR	01	4.00Ex16"	05/94x140x18.5-E1	0	169	735	615	4	58	18	
12419		7.50 - 16" 8PR	5.50Fx16"		06/161x205x21.5-E2	214		804	1023	2,3	34	22		
22,5"	8021	500/60 - 22,5" TL 16PR	04	16.00x22,5"	08/221x275x27-A3	0	503	1192	4875	3,4	50	110		
	7019	550/60 - 22,5" TL 16PR					537	1254	5450	3,9	56	115		

NOTAS DE INTERES: / NOTES OF INTEREST:

* Los dibujos de los neumáticos reflejados en este catálogo son orientativos. / The tyre tread patterns show in this catalogue are for illustrative purposes only.