



C-MPDVR SERIES

MPEG4 Digital Video Recorders



KEY FEATURES:

- MPEG4 compression
- Pentaplex (5 functions)
- Network access with IE or Client
- IR remote control (except C-MPDVR Lite)
- Search via time/date, motion or alarm
- Built in DVD writer for event back up (except C-MPDVR04-Lite)
- Dual monitor output (with VGA adaptor)
- Expandable external storage
- Firmware upgrade via USB
- Password protection
- Realtime recording in CIF mode

The C-MP DVR series of 4, 8 & 16 channel MPEG4 Pentaplex DVRs combine the latest compression technology with a simple user interface. The units come with a built-in DVD-RW (except C-MPDVR-04-lite) and HDD providing storage of up to 500GB.

The Pentaplex function (Pentaplex means view, record, archive locally, view and record remotely) allows the operator to view live information & playback information on the same display whilst backing up a previous event. During this time the record process is uninterrupted and an additional operator could be viewing via the network connection.

The MPEG4 compression allows the DVR to achieve maximum recording efficiency for the available hard disk drive. Space is extended when compared to other compression techniques.

The recording function can be programmed for continuous, alarm or motion recording. Additionally these recordings can be scheduled to start and stop and different parts of the day. Event backup is done via the built in DVD Writer.

Optional Accessories:

Disk Array - External storage devise in 19" Rack mount, 2U high and providing upto 1.5TB capacity.


VGA Adaptor - composite to VGA adaptor for viewing images on a PC screen

Ordering Information

C-MPDVR-04/160-Lite	4 channel MPEG4 DVR, 160 GB (without DVD-RW)
C-MPDVR-08/250	8 channel MPEG4 DVR with DVD-RW, 250GB
C-MPDVR-08/500	8 channel MPEG4 DVR with DVD-RW, 500GB
C-MPDVR-16/500	16 channel MPEG4 DVR with DVD-RW, 500GB
C-MPDVR-ARRAY	Additional disk storage Array
C-MPDVR-VGA	VGA Adaptor to allow the use of a PC Monitor

Contact CBC for storage options on both DVR and Disk Array

Rear view



- 1 - Disk Array port
- 2 - Connection to IR receiver
- 3 - RS485
- 4 - External I/O port
- 5 - USB port
- 6 - D/V port
- 7 - Lan
- 8 - Link /Act led light
- 9 - Call monitor
- 10 - Power
- 11 - Fan
- 12 - Video input
- 13 - Loop
- 14 - 75 Ω / HI
- 15 - Monitor
- 16 - Audio in
- 17 - Audio out

OPTIONAL PERIPHERALS



Disk Array



VGA adaptor



C-MPDVR SERIES

MPEG4 Digital Video Recorders

MODEL	C-MPDVR04-LITE	C-MPDVR04	C-MPDVR08	C-MPDVR16
Video format	PAL/NTSC			
Compression system	MPEG4			
DVR type	PENTAPLEX			
Operating system Embedded	Linux			
HDD	IDE Type, ATA66, Support HDD x 1			
Video input	4x Composite 1.0Vp-p auto terminating	8x Composite 1.0Vp-p auto terminating	16x Composite 1.0Vp-p auto terminating	
Video output	Main monitor output & Call monitor output: Composite video signal 1 Vp-p 75 ohms BNC			
Audio in/out	2 audio inputs, 1 audio output (mono)		4 audio inputs, 2 audio outputs (mono)	
Record modes	Continuous, Manual / Timer / Motion / Alarm			
DVD Writer	No	Yes	Yes	Yes
Watermark	Yes			
Record rate				
Frame (720 x 576)	25ips PAL/ 30ips NTSC		50ips PAL/ 60ips NTSC	100ips PAL/ 120ips NTSC
CIF (352 x 288)	100ips PAL/ 120ips NTSC		200ips PAL/ 240ips NTSC	400ips PAL/ 480ips NTSC
Motion detection	Yes, programmable per camera, 16 x 12 grids per camera			
Motion detect sensitivity	4 adjustable variable with precise calculation for motion detection			
Pre-alarm recording	Yes (8MB)			
Network protocol	TCP/IP, PPPoE, DHCP and DDNS			
Software update	USB / Network			
Alarm Notification	By email or FTP upload			
Alarm in/out	4 inputs, 1 output		8 inputs, 1 output	16 inputs, 1 output
Remote control	No	Yes	Yes	Yes
Ethernet	10/100 Base-T. Support remote control and live view via Ethernet			
Picture Zoom	2x digital zoom			
Camera title	Supports upto 6 letters			
Video loss detection	Yes			
Video adjustment	Hue / Colour / Contrast / Brightness			
Date Display format	YY/MM/DD, DD/MM/YY, MM/DD/YY, and OFF			
Daylight saving	Yes			
System recovery	Auto, after power reconnected			
Optional peripherals	VGA connector	Independent Disk Array, VGA connector		
Dimensions	432mm (w) x 90mm (h) x 326mm (d)			
Weight / mounting	4Kg (no HDD) / Desk mount			
Power consumption	64W including HDDs			
Input voltage	19VDC or 100-260VAC with supplied power adaptor			
Operating conditions	0 - 40 degrees C			

Recording times for 160GB

Record speeds	16 channel					8 channel					4 channel		
	100 ips	50 ips	25 ips	12.5 ips	6 ips	25 ips	12.5 ips	6 ips	25 ips	12.5 ips	6 ips	3 ips	
720 x 576 Frame	100	50	25	12.5	6	25	12.5	6	25	12.5	6	3	
350 x 288 CIF	200	100	50	25	12.5	50	25	12.5	25	12.5	6	3	
Record quality	Record time in days and hours												
Best	1d 17hrs	3d 1hrs	5d 14hrs	9d 0hrs	3d 11hrs	6d 3hrs	11d 4hrs	18d 1hrs	6d 23hrs	12d 6hrs	22d 8hrs	36d 3hrs	
High	2d 2hrs	3d 15hrs	7d 16hrs	10d 18hrs	4d 4hrs	7d 7hrs	13d 8hrs	21d 13hrs	8d 8hrs	14d 15hrs	26d 16hrs	43d 2hrs	
Normal	2d 22hrs	5d 3hrs	9d 9hrs	15d 4hrs	5d 20hrs	10d 7hrs	18d 19hrs	30d 9hrs	11d 17hrs	20d 15hrs	37d 14hrs	60d 17hrs	
Basic	2d 21hrs	5d 2hrs	9d 7hrs	15d 0hrs	5d 19hrs	10d 4hrs	18d 14hrs	30d 0hrs	11d 14hrs	20d 9hrs	37d 4hrs	60d 1hrs	

Recording times for 250GB

Record speeds	16 channel					8 channel					4 channel		
	100 ips	50 ips	25 ips	12.5 ips	6 ips	25 ips	12.5 ips	6 ips	25 ips	12.5 ips	6 ips	3 ips	
720 x 576 Frame	100	50	25	12.5	6	25	12.5	6	25	12.5	6	3	
350 x 288 CIF	200	100	50	25	12.5	50	25	12.5	25	12.5	6	3	
Record quality	Record time in days and hours												
Best	2d 17	4d 19h	8d 17h	14d 2h	5d 11h	9d 14h	17d 11h	28d 5h	10d 22h	19d 4h	34d 22h	56d 11h	
High	3d 6h	5d 17h	10d 10h	16d 19h	6d 12h	11d 10h	20d 20h	33d 15h	13d 0h	22d 21h	41d 16h	67d 7h	
Normal	3d 10h	6d 1h	11d 1h	17d 20h	6d 21h	12d 3h	22d 2h	35d 17h	13d 19h	24d 6h	44d 5h	71d 10h	
Basic	4d 14h	8d 1h	14d 16h	23d 17h	9d 4h	16d 3h	29d 8h	47d 10h	18d 8h	32d 6h	58d 17h	94d 21h	

Recording times for 500GB

Record speeds	16 channel					8 channel					4 channel		
	100 ips	50 ips	25 ips	12.5 ips	6 ips	25 ips	12.5 ips	6 ips	25 ips	12.5 ips	6 ips	3 ips	
720 x 576 Frame	100	50	25	12.5	6	25	12.5	6	25	12.5	6	3	
350 x 288 CIF	200	100	50	25	12.5	50	25	12.5	25	12.5	6	3	
Record quality	Record time in days and hours												
Best	5d 11h	9d 14h	17d 11h	28d 5h	10d 22h	19d 4h	34d 22h	56d 11h	21d 20h	38d 9h	69d 21h	112d 22h	
High	6d 12h	11d 10h	20d 20h	33d 15h	13d 0h	22d 21h	41d 16h	67d 7h	26d 1h	45d 16h	83d 8h	134d 15h	
Normal	6d 21h	12d 3h	22d 2h	35d 17h	13d 19h	24d 6h	44d 5h	71d 10h	27d 15h	48d 13h	88d 10h	142d 21h	
Basic	9d 4h	16d 3h	29d 8h	47d 10h	18d 8h	32d 6h	58d 17h	94d 21h	36d 17h	64d 12h	117d 11h	189d 19h	

