

Product Profile

- Available in multiple configurations
- Wall mount configuration for step van and settlement room applications
- Easy loading of up to 3-ply paper from internal or external paper trays
- 512k flash memory can store DBCS fonts such as Korean and Chinese
- Optional HHC holders and docks for Intermec® 6000, 600, 700 Series mobile computers
- Fast two-page-per-minute print time helps get the work done fast
- Easy Flexibility



6 8 2 0 P R I N T E R

The Intermec® 6820 printer produces high-quality customer invoices, receipts, load reports, transfers and other documents for route accounting applications. Data input is provided by the Intermec 6000 Series mobile computers via holders and vehicle docks.

Portable

The Intermec 6820 portable printer provides flexibility and mobility. It features a handle for easy carrying and a compact tray which holds enough paper for an entire day. A seat-mount strap is available to secure the printer in vehicles with bench seats. An optional, soft-sided carrying case provides a sealed compartment inside the case cover for storage of invoices.

Fixed Mount

The fixed mount model is ideal for applications where mounting the printer in a vehicle is preferred. The mobile computer holder can be mounted either

to the side of the printer or remote from the printer, whichever is most convenient. Although the printer is safely mounted to the vehicle, a quick release feature allows one-step removal of the printer for swapping from one vehicle to another.

Wall Mount

The wall mount printer can be mounted on rugged vertical surfaces in trucks and settlement rooms. It is ideal for installations where space is limited. A quick release allows one-step removal for swapping from one vehicle to another. Optional paper trays hold paper for multiple route days. All configurations work with existing software applications for the Intermec 4820 printer.

Portable (245-190-200)

Optional handle, AC foot, 61xx or 62xx terminal holder top mount.

Physical Characteristics

Standard: Handle, 62xx holder top mount or fill plate

Length: 38.1cm (15")

Width: 41.9cm (16.5")

Depth: 13cm (5.13")

Weight: 5.67kg (12.25 lbs.)

Portable with AC Foot (245-190-201)**Physical Characteristics**

Length: 38.1cm (15")

Width: 48.3cm (19")

Depth: 13cm (5.13")

Weight: 5.67kg (12.25 lbs.)

Custom: Handle, 61xx holder top mount

Length: 42.6cm (16.75")

Width: 48.3cm (19")

Depth: 20.3cm (8")

Weight: 5.80kg (12.75 lbs.)

Wall Mount (245-190-204)**Physical Characteristics**

Length: 26.7cm (10.5")

Width: 33.7cm (13.25")

Depth: 11.4cm (4.5")

Weight: 6.42kg (14.15 lbs.)

Fixed Mount (245-190-202)

- Base is 32.5cm (12.75") x 35.5cm (14"). The upper portion may include either the 61xx or 62xx terminal holder.

- Refer to the 6820 printer user's guide (961-019-013) for specific configurations for the following:

- Custom with 61xx terminal holder side mount

- Custom with 61xx or 62xx terminal holder top mount

Physical Characteristics

Length: 36.8cm (14.5")

Width: 47cm (18.5")

Depth: 20.3cm (8")

Weight: 6.55kg (14.4 lbs.)

Fixed Mount (245-190-203)

62XX hhc terminal holder side mount

Physical Characteristics

Length: 36.8cm (14.5")

Width: 47cm (18.5")

Depth: 20.3cm (8")

Weight: 6.55kg (14.41 lbs.)

Fixed Mount (245-190-400)**Physical Characteristics**

Length: 42.6cm (16.75")

Width: 42.5cm (16.75")

Depth: 19.1cm (7.5")

Weight: 6.55kg (14.41 lbs.)

Portable (245-190-401)**Physical Characteristics**

Length: 42.6cm (16.75")

Width: 41.9cm (16.5")

Depth: 20.3cm (8")

Weight: 5.8kg (12.75 lbs.)

Portable (245-190-402)**Physical Characteristics**

Length: 42.6cm (16.75")

Width: 41.9cm (16.5")

Depth: 20.3cm (8")

Weight: 5.8kg (12.75 lbs.)

Environment**DC Operating Temperature:**

-20° to 60°C (-4° to 140°F)

AC Operating Temperature:

-20° to 45°C (-4° to 113°F)

Storage Temperature:

-30° to 70°C (-22° to 158°F)

Power

Vehicle: low amperage draw; protection from voltage irregularities

Lead Acid Battery: 12-volt standard cam-corder type. Full charge will print dozens of tickets. Time to recharge is one hour.

AC Adapter: 115/230 volt

Printer Mechanism

Characteristics: Dot matrix, Bi-directional, Graphics capable

Print speed: 2 pages per minute

Type styles: char/line: Normal 80, Bold 40, Condensed 136, Bold condensed 68

Paper

1 to 3-ply fan fold, 7.5" to 8.5" x 11", Carbonless, NCR paper with adhesive tacking on left border

Ribbon

- One color cartridge, black, one million character life
- One color cartridge, purple, one million character life

Regulatory Approvals

FCC Class B, CE mark

Note

Some approvals and features may vary by country and may change without notice. Specs may vary based upon the specific configuration or features selected. Please check with your local Intermec sales office for further information.

North America

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551

Systems & Solutions

550 2nd Street S.E.
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453

Media Supplies

9290 Le Saint Drive
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487

**Europe/
Middle East & Africa**

Headquarters
Sovereign House
Vastern Road
Reading, Berkshire RG1 8BT
United Kingdom
tel: +44.118.987.9400
fax: +44.118.987.9401

Gothenburg

Idrottsvägen 10
P.O. Box 123
SE-431 22 Mölndal
Sweden
tel: +46.31.869500
fax: +46.31.869595

**Asia Pacific/
Latin America**

Hong Kong
26-12 Shell Tower
Times Square
1 Matheson Street
Causeway Bay
Hong Kong
tel: 852.2574.9777
fax: 852.2574.9725

Singapore

25-16 International Plaza
10 Anson Road, 079903
tel: 65.324.8391
fax: 65.324.8393

Australia

Level 7, 200 Pacific Highway
Crows Nest NSW 2065
Australia
tel: 61.2.9901.2065
fax: 61.2.9954.6300

South America and Mexico

2572 White Road
Irvine, California 92614
tel: 949.975.1905
fax: 949.975.1913

Worldwide

Fax Document Retrieval Service
800.755.5505
(North America Only)
tel: 650.556.8447

Internet

www.intermec.com

Sales

800.347.2636
(toll free in N.A.)
425.348.2726

Service and Support

800.755.5505
(toll free in N.A.)
425.356.1799

Copyright © 2001 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 608961-01C 05/01

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.