

The Intermec logo is positioned vertically on the left side of the page. It features the word "Intermec" in a bold, sans-serif font, with a stylized graphic element below it consisting of a blue square containing a white circular pattern resembling a globe or a network. The logo is partially overlaid by a large, faint outline of a hand holding a pen, which is part of the overall design theme of the document.

Intermec

Product Profile

- Economical, yet highly functional
- Lightweight, belt-clip design makes it easy to carry
- Rugged housing built for the field environment
- 4" (10.2 cm) paper width capability
- 40-column format, with optional compressed 80-column capability
- Compatible with the Intermec® 6804T, 6805a and 6806 printers
- Linerless label option



6 8 0 8 P R I N T E R

Economical Yet Functional

The Intermec® 6808 thermal printer is the newest addition to the Intermec line of belt-clip printers. It is small, lightweight, durable and weather resistant, so it is easily incorporated into field use. Its reliable printer mechanism offers exceptional print clarity with the versatility of printing graphics, bar codes and logos.

It can quickly print both standard and bar-coded receipts, yet provides users with a 4-inch paper width capability to accommodate 40-column formats.

80-column Alternative

The unit offers the ability to provide a compressed 80-column receipt, without the field worker having to carry the bulk of a larger 80-column printer.

Long-Lasting Power Supply

The Intermec 6808 has a vehicle charger option that ensures a long day's work in the field. It has a sleep mode for battery conservation, and the unit wakes itself up when it senses data input.

Easy to Use

The Intermec 6808 is fully compatible with the Intermec 6804T, 6805a and 6806 printers. In addition, its functional design makes paper loading simple, since roll-type paper fits easily into place. And its one-year warranty provides additional peace of mind.

Intermec

Physical Characteristics**Length:** 16.5cm (6.5")**Width:** 16.9cm (6.7")**Depth:** 6.7cm (2.6")**Weight:** With one battery 580g (20.6oz)**Environment****Operating Temperature:**

14° to 140° F (-10° to 60°C)

Drop Spec: Withstands multiple 183cm (6') drops to concrete**Power Source**

Internal battery, Lilon 1.8 amp/hr, 7.2v, 1350mAh

User replaceable

Battery Recharging

Nine hours to full charge using a vehicle cigarette lighter power adapter or standard AC power adapter

Printer Mechanism Characteristics

Direct thermal line printer

203 dots per inch (dpi)

Print Speed: 5.1cm (2") per second**Fonts**

Three resident fonts

Up to four additional fonts may be downloaded

Print Capabilities

Characters, graphics and bar codes

Print Medium

Thermal paper, one ply

Paper Width: 11.2cm (4.4")**Print Duration Per Charge**

Over 9144cm (3,600")

Interface

IrDA®

RS-232 serial

Chargers

AC wall charger

12V vehicle charger

Regulatory Approvals

FCC Title 47, Part 15, Subpart B, Class B

EN 55022 Class B

EN 50082-1

EN 60950

Warranty

One year warranty. Additional service packages available.

Some approvals and features may vary by country and may change without notice. Specs may vary based upon the specific configuration or features selected. Please check with your local Intermec sales office for further information.

North America

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551

Systems & Solutions

550 2nd Street S.E.
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453

Media Supplies

9290 Le Saint Drive
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487

**Europe/
Middle East & Africa**

Headquarters
Sovereign House
Vastern Road
Reading, Berkshire RG1 8BT
United Kingdom
tel: +44.118.987.9400
fax: +44.118.987.9401

Gothenburg

Idrottsvägen 10
P.O. Box 123
SE-431 22 Mölndal
Sweden
tel: +46.31.869500
fax: +46.31.869595

Asia

Hong Kong
26-12 Shell Tower
Times Square
1 Matheson Street
Causeway Bay
Hong Kong
tel: 852.2574.9777
fax: 852.2574.9725

Singapore

25-16 International Plaza
10 Anson Road, 079903
tel: 65.324.8391
fax: 65.324.8393

Australia

Level 7, 200 Pacific Highway
Crows Nest NSW 2065
Australia
tel: 61.2.9901.2065
fax: 61.2.9954.6300

South America & Mexico

Latin America Headquarters
17921 B Skypark Circle
Irvine, California 92614
tel: 949.442.9393
fax: 949.757.1687

Mexico

Tamulipas 141, Primero Piso
06140 Mexico, D.F.
tel: 525.55.211.1919
fax: 525.55.211.8121

Worldwide

Fax Document Retrieval Service
800.755.5505
(North America Only)
tel: 650.556.8447

Internet

www.intermec.com

Sales

800.347.2636
(toll free in N.A.)
tel: 425.348.2726

Service and Support

800.755.5505
(toll free in N.A.)
tel: 425.356.1799

Copyright © 2002 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 608960-01B 02/02

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.