















Accesorios generales para la instalación de la luminaria modelo OVAL
 General accessories for OVAL luminaire installations

Detalle / Detail	Ref	Color	Detalle / Detail	Ref	Color
 <p>Tapa final End cover</p> <p>160 mm 69 mm</p>	52.06.40.0	<input type="checkbox"/>	 <p>Perfil y tapa Profile and cover</p> <p>52.05.00.0 52.05.10.0</p> <p>max. 3m</p>	52.05.00.0 52.05.10.0	<input type="checkbox"/> <input type="checkbox"/>
 <p>Unión codo 90° 90° elbow joint</p> <p>175 mm</p>	52.05.20.0	<input type="checkbox"/>	 <p>Unión "T" "T" joint</p> <p>175 mm 190 mm</p>	52.05.21.0	<input type="checkbox"/>
 <p>Unión "Cruz" "Cross" joint</p> <p>190 mm</p>	52.05.22.0	<input type="checkbox"/>	 <p>Rótula Ball joint</p> <p>50</p>	96.06.04.0	<input type="checkbox"/>
 <p>Tapa unión rótula Cover with ball joint</p> <p>Máx: 6 unid. mín. 55°</p> <p>170 mm</p>	52.06.41.0	<input type="checkbox"/>	 <p>Juego de 2 fijaciones para unión Set of 2 fixings per joint</p>	52.06.01.0	
 <p>Tapa con downlight orientable bajo voltaje Cover with spot light adjustable positioning</p> <p>300 mm</p> <p>50W 12V</p> <p>QR-CBCs Electronic</p>	52.07.02.0	<input type="checkbox"/>	 <p>Soportes pared con tapa incorporada Wall supports with cover included</p> <p>52.04.80.0 Final End 52.07.41.0 Intermedia Intermediate part</p>	52.04.80.0 52.07.41.0	<input type="checkbox"/> <input type="checkbox"/>
 <p>Tapa con proyector Twin Cover with projector Twin</p> <p>300 mm</p> <p>50W 12V</p> <p>QR-CBCs Electronic</p>	52.07.03.0	<input type="checkbox"/>	 <p>Unión soporte pared Wall bracket</p> <p>300 mm</p> <p>2 unit. / ref.</p>	96.07.46.0	<input type="checkbox"/>
 <p>Soporte a pared orientable Wall support adjustable</p> <p>13 cm</p> <p>2 unit. / ref.</p> <p>+90° 0° -90°</p>	96.00.06.0	<input type="checkbox"/>	 <p>Soporte a pared orientable y extensible Wall support adjustable and extensible</p> <p>min. 30 cm max. 40 cm</p> <p>2 unit. / ref.</p> <p>+90° 0° -90°</p>	96.00.05.0	<input type="checkbox"/>

Suspensiones pág. 344
 Suspensions pag. 344