



Aplique BLOC de pared con radiación directa extensiva e indirecta intensiva  
BLOC wall mounted luminaire with direct-wide and indirect-narrow distribution



Lamp	Equipo / Gear	Ref	Color	W	Plum																															
	Electromagnético Electromagnetic	67.02.03.3	■	18	25,3W	<div style="display: flex; align-items: flex-start;"> <div style="margin-right: 10px;"> <p>6702003 Semiplanos C</p> </div> <div> <table border="1"> <thead> <tr> <th>h(m)</th> <th>Max</th> <th>Med</th> <th>D(m)</th> <th>D(m)</th> </tr> </thead> <tbody> <tr><td>1</td><td>489</td><td>159</td><td>1.52</td><td>3.14</td></tr> <tr><td>2</td><td>122</td><td>40</td><td>3.04</td><td>6.28</td></tr> <tr><td>3</td><td>54</td><td>18</td><td>4.56</td><td>9.41</td></tr> <tr><td>4</td><td>31</td><td>10</td><td>6.08</td><td>12.55</td></tr> <tr><td>5</td><td>20</td><td>6</td><td>7.60</td><td>15.69</td></tr> </tbody> </table> <p>                     Im = 3300.u.u                      Imax = 179.74 cd/kim                      U = 0.31 D + 0.03 T                      Eta = 34.66%                      G=0.0°                      Alpha=37.2°+37.2°                      Beta=57.5°+57.5°                 </p> </div> </div>	h(m)	Max	Med	D(m)	D(m)	1	489	159	1.52	3.14	2	122	40	3.04	6.28	3	54	18	4.56	9.41	4	31	10	6.08	12.55	5	20	6	7.60	15.69
h(m)	Max	Med	D(m)	D(m)																																
1	489	159	1.52	3.14																																
2	122	40	3.04	6.28																																
3	54	18	4.56	9.41																																
4	31	10	6.08	12.55																																
5	20	6	7.60	15.69																																

	Electromagnético Electromagnetic	67.02.00.3	■	35	55,2W	
--	-------------------------------------	------------	---	----	-------	--

	Directo a red Mains supply	67.02.02.3	■	max. 60	60W	