




Bañador de pared o techo para líneas continuas fabricado en extrusión de aluminio lacado en color gris RAL 9006 y tapas de policarbonato. Dispone de difusor de policarbonato en ambas aperturas laterales de la luminaria sustituibles por tapas ciegas para obtención de un solo haz de luz directa o indirecta. Disponible en módulos finales y módulos intermedios. Equipado para lámparas fluorescentes T5-HO y T8.

Wall or ceiling washer for continuous lines, manufactured in extruded aluminium lacquered in grey RAL 9006, with polycarbonate covers. Has polycarbonate diffusers on both of the luminaire's side openings. These diffusers can be replaced with blind covers to give a single direct or indirect beam. Available as end modules and intermediate modules. Equipped for fluorescent lamps T5-HO and T8.



Bañador de pared o techo AMBIENT intermedia para línea continua
 AMBIENT wall washer or ceiling washer intermediate for continuous mounting





Lamp	Equipo / Gear	Ref	Color	W	Plum	Lmm.																															
G13 T8/T26	Electromagnético	88.01.90.0	<input type="checkbox"/>	1x18	27,6W	700	<p>8801913 Semiplanos C</p> <p>h(m)</p> <table border="1"> <tr><th>h(m)</th><th>Max</th><th>Med</th><th>D(m)</th><th>D(m)</th></tr> <tr><td>1</td><td>529</td><td>192</td><td>1,28</td><td>2,58</td></tr> <tr><td>2</td><td>132</td><td>48</td><td>2,56</td><td>5,16</td></tr> <tr><td>3</td><td>59</td><td>21</td><td>3,85</td><td>7,74</td></tr> <tr><td>4</td><td>33</td><td>12</td><td>5,13</td><td>10,32</td></tr> <tr><td>5</td><td>21</td><td>8</td><td>6,41</td><td>12,90</td></tr> </table> <p>Im = 3350.00 Imax = 158.00 cd/Klm F UTE 0.29 I + 0.29 T Eta = 56.50% Alpha=32.7°+32.7° Beta=52.2°+52.2° G=0.0°</p>	h(m)	Max	Med	D(m)	D(m)	1	529	192	1,28	2,58	2	132	48	2,56	5,16	3	59	21	3,85	7,74	4	33	12	5,13	10,32	5	21	8	6,41	12,90
	h(m)	Max	Med	D(m)	D(m)																																
1	529	192	1,28	2,58																																	
2	132	48	2,56	5,16																																	
3	59	21	3,85	7,74																																	
4	33	12	5,13	10,32																																	
5	21	8	6,41	12,90																																	
Electromagnetic	88.01.90.3	<input type="checkbox"/>	1x18	27,6W	700																																
		88.01.91.0	<input type="checkbox"/>	1x36	36,8W	1300																															
		88.01.91.3	<input type="checkbox"/>	1x36	36,8W	1300																															
	AMBIENT intermedio	88.01.92.0	<input type="checkbox"/>	1x58	75,9W	1600																															
	Ambient intermediate	88.01.92.3	<input type="checkbox"/>	1x58	75,9W	1600																															
	AMBIENT final	88.01.93.0	<input type="checkbox"/>	1x18	27,6W	725																															
	Ambient end	88.01.93.3	<input type="checkbox"/>	1x18	27,6W	725																															
		88.01.94.0	<input type="checkbox"/>	1x36	36,8W	1325																															
		88.01.94.3	<input type="checkbox"/>	1x36	36,8W	1325																															
		88.01.95.0	<input type="checkbox"/>	1x58	75,9W	1625																															
		88.01.95.3	<input type="checkbox"/>	1x58	75,9W	1625																															


G5	Electrónico T5 HO	88.41.60.0	<input type="checkbox"/>	1x24	27,6W	650	<p>8841610 Semiplanos C</p> <p>h(m)</p> <table border="1"> <tr><th>h(m)</th><th>Max</th><th>Med</th><th>D(m)</th><th>D(m)</th></tr> <tr><td>1</td><td>289</td><td>100</td><td>2,07</td><td>2,37</td></tr> <tr><td>2</td><td>72</td><td>25</td><td>4,13</td><td>4,74</td></tr> <tr><td>3</td><td>32</td><td>11</td><td>6,20</td><td>7,12</td></tr> <tr><td>4</td><td>18</td><td>6</td><td>8,26</td><td>9,49</td></tr> <tr><td>5</td><td>12</td><td>4</td><td>10,33</td><td>11,86</td></tr> </table> <p>Im = 4460.00 Imax = 65.80 cd/Klm F UTE 0.18 J + 0.17 T Eta = 34.77% Alpha=45.9°+45.9° Beta=49.9°+49.9° G=0.0°</p>	h(m)	Max	Med	D(m)	D(m)	1	289	100	2,07	2,37	2	72	25	4,13	4,74	3	32	11	6,20	7,12	4	18	6	8,26	9,49	5	12	4	10,33	11,86
	h(m)	Max	Med	D(m)	D(m)																																
1	289	100	2,07	2,37																																	
2	72	25	4,13	4,74																																	
3	32	11	6,20	7,12																																	
4	18	6	8,26	9,49																																	
5	12	4	10,33	11,86																																	
T5/T16	Electronic T5 HO	88.41.60.3	<input type="checkbox"/>	1x24	27,6W	650																															
		88.41.61.0	<input type="checkbox"/>	1x54	61W	1250																															
		88.41.61.3	<input type="checkbox"/>	1x54	61W	1250																															
	AMBIENT intermedio	88.41.62.0	<input type="checkbox"/>	1x80	88W	1550																															
	Ambient intermediate	88.41.62.3	<input type="checkbox"/>	1x80	88W	1550																															
	AMBIENT final	88.41.63.0	<input type="checkbox"/>	1x24	27,6W	650																															
	Ambient end	88.41.63.3	<input type="checkbox"/>	1x24	27,6W	650																															
		88.41.64.0	<input type="checkbox"/>	1x54	61W	1250																															
		88.41.64.3	<input type="checkbox"/>	1x54	61W	1250																															
		88.41.65.0	<input type="checkbox"/>	1x80	88W	1550																															
		88.41.65.3	<input type="checkbox"/>	1x80	88W	1550																															

1-10V Referencias regulables p.481
 Dimable references p.481

Accesorios
Accessories

Detalle / Detail	Ref.	Color	W	Lmm	Lamp
 <p>Tapa ciega para radiación directa o indirecta Blind cover for direct or indirect light</p> <p>IP 40</p>	88.06.36.0	<input type="checkbox"/>	36	500	TC-L
	88.06.36.3	<input checked="" type="checkbox"/>	36	500	TC-L
	88.06.33.0	<input type="checkbox"/>	18	700	T8/T26
	88.06.33.3	<input checked="" type="checkbox"/>	18	700	T8/T26
	88.06.34.0	<input type="checkbox"/>	36	1300	T8/T26
	88.06.34.3	<input checked="" type="checkbox"/>	36	1300	T8/T26
	88.06.35.0	<input type="checkbox"/>	58	1600	T8/T26
	88.06.35.3	<input checked="" type="checkbox"/>	58	1600	T8/T26
	88.06.30.0	<input type="checkbox"/>	24	650	T5/T16
	88.06.30.3	<input checked="" type="checkbox"/>	24	650	T5/T16
	88.06.31.0	<input type="checkbox"/>	54	1250	T5/T16
	88.06.31.3	<input checked="" type="checkbox"/>	54	1250	T5/T16
	88.06.32.0	<input type="checkbox"/>	80	1550	T5/T16
	88.06.32.3	<input checked="" type="checkbox"/>	80	1550	T5/T16



 <p>Juego de 2 fijaciones para unión Set of 2 fixings per joint</p>	96.06.01.0	<input checked="" type="checkbox"/>			
--	------------	-------------------------------------	--	--	--

