




Luminaria modelo DINAMIC TECH para suspender o adosar a techo con celosía de alto confort visual. Fabricada en aluminio extrusionado, anodizado plata mate, de radiación directa o directa-indirecta. Reflector interior de aluminio brillante especular, equipada para lámparas fluorescentes T5 de 14W o 28W.

DINAMIC TECH suspended or surface mounted luminaire with double parabolic louvre. Made of extruded aluminium, silver matt anodised. Direct or direct-indirect light. Interior reflector in bright specular aluminium, equipped for 14w or 28w T5 fluorescent lamps.



Luminaria DINAMIC TECH con celosía de alto confort visual  
DINAMIC TECH luminaire with double parabolic louvre



Lamp	Equipo / Gear	Ref	Color	W	Plum	L x A x H mm																																	
	Electrónico T5 HO	64.44.02.0	□	4 x 14	66,7 W	650 x 650 x 57			<table border="1"> <tr> <th>h[m]</th> <th>Max</th> <th>Med</th> <th>D[m]</th> <th>D[m]</th> </tr> <tr> <td>1</td> <td>1245</td> <td>721</td> <td>2.23</td> <td>1.50</td> </tr> <tr> <td>2</td> <td>311</td> <td>180</td> <td>4.46</td> <td>3.01</td> </tr> <tr> <td>3</td> <td>138</td> <td>80</td> <td>6.68</td> <td>4.51</td> </tr> <tr> <td>4</td> <td>78</td> <td>45</td> <td>8.91</td> <td>6.01</td> </tr> <tr> <td>5</td> <td>50</td> <td>29</td> <td>11.14</td> <td>7.52</td> </tr> </table>	h[m]	Max	Med	D[m]	D[m]	1	1245	721	2.23	1.50	2	311	180	4.46	3.01	3	138	80	6.68	4.51	4	78	45	8.91	6.01	5	50	29	11.14	7.52
	h[m]	Max	Med	D[m]	D[m]																																		
1	1245	721	2.23	1.50																																			
2	311	180	4.46	3.01																																			
3	138	80	6.68	4.51																																			
4	78	45	8.91	6.01																																			
5	50	29	11.14	7.52																																			
Electronic T5 HO	64.43.02.0	□	3 x 14	52,9 W	650 x 650 x 57	<p>6444020</p> <p>Semiplanos C</p> <p>Im = 540.00 Imax = 329.66 cd/klm</p> <p>F UTE 0.64 C + 0.00 T Eta = 64.49%</p> <p>G=0.0° Alpha=48.1°+48.1° Beta=36.9°+36.9°</p>																																	
	Radiación directa Direct Luminaire																																						
	Electrónico T5 HO	64.42.02.0	□	2 x 28	64,4 W	1250 x 350 x 57			<table border="1"> <tr> <th>h[m]</th> <th>Max</th> <th>Med</th> <th>D[m]</th> <th>D[m]</th> </tr> <tr> <td>1</td> <td>3726</td> <td>1490</td> <td>1.63</td> <td>1.71</td> </tr> <tr> <td>2</td> <td>932</td> <td>373</td> <td>3.26</td> <td>3.41</td> </tr> <tr> <td>3</td> <td>414</td> <td>166</td> <td>4.89</td> <td>5.12</td> </tr> <tr> <td>4</td> <td>233</td> <td>93</td> <td>6.53</td> <td>6.83</td> </tr> <tr> <td>5</td> <td>149</td> <td>60</td> <td>8.16</td> <td>8.53</td> </tr> </table>	h[m]	Max	Med	D[m]	D[m]	1	3726	1490	1.63	1.71	2	932	373	3.26	3.41	3	414	166	4.89	5.12	4	233	93	6.53	6.83	5	149	60	8.16	8.53
	h[m]	Max	Med	D[m]	D[m]																																		
1	3726	1490	1.63	1.71																																			
2	932	373	3.26	3.41																																			
3	414	166	4.89	5.12																																			
4	233	93	6.53	6.83																																			
5	149	60	8.16	8.53																																			
Electronic T5 HO	64.42.02.0	□	2 x 28	64,4 W	1250 x 350 x 57	<p>6442020</p> <p>Semiplanos C</p> <p>Im = 5800.00 Imax = 642.47 cd/klm</p> <p>F UTE 0.98 B + 0.00 T Eta = 64.49%</p> <p>G=0.0° Alpha=39.2°+39.2° Beta=40.5°+40.5°</p>																																	
	Radiación directa Direct Luminaire																																						
	Electrónico T5 HO	64.44.03.0	□	4 x 14	66,7 W	650 x 650 x 57																																	
	Electronic T5 HO	64.44.03.0	□	4 x 14	66,7 W	650 x 650 x 57																																	
	Radiación directa-indirecta Direct-indirect Luminaire	Difusor superior de policarbonato transparente incluido Transparent polycarbonate upper diffuser included																																					
	Electrónico T5 HO	64.42.03.0	□	2 x 28	64,4 W	1250 x 350 x 57																																	
	Electronic T5 HO	64.42.03.0	□	2 x 28	64,4 W	1250 x 350 x 57																																	
	Radiación directa-indirecta Direct-indirect Luminaire	Difusor superior de policarbonato transparente incluido Transparent polycarbonate upper diffuser included																																					