




Proyector de superficie con un LED de 1 W y fuente de alimentación incorporada. El cuerpo y el aro están fabricados en inyección de la temperatura. Modelos lacados en color gris, disponibles en blanco neutro 4200°K y blanco frío 5400°K. Existe una gran variedad de ópticas intensivas, semi-extensivas, extensivas y elípticas para satisfacer todas las necesidades lumínicas.

Surface spot light with a 1W LED and incorporated power supply. The body and the trim ring are manufactured in die cast zamak for good heat dissipation. Models lacquered in grey, available in neutral white 4200°K and cool white 5400°K. There is a great variety of intensive, semi-extensive, extensive and elliptical optics to satisfy all lighting requirements.



Proyector FINE LEDS orientable 1 LED
FINE LEDS adjustable projector 1 LED



Lamp.	Equipo / Gear	Ref	Color	W	Plum	K°	Cd.	Δ																																	
LED	Electrónico	86.41.30.3	■	1	1,2W	4200	100	70°	8641313 Semiplanos C		<table border="1"> <thead> <tr> <th>h(m)</th> <th>Max</th> <th>Med</th> <th>D(m)</th> <th>D(m)</th> </tr> </thead> <tbody> <tr><td>1</td><td>33</td><td>20</td><td>1.57</td><td>1.57</td></tr> <tr><td>2</td><td>8</td><td>5</td><td>3.15</td><td>3.15</td></tr> <tr><td>3</td><td>4</td><td>2</td><td>4.72</td><td>4.72</td></tr> <tr><td>4</td><td>2</td><td>1</td><td>6.30</td><td>6.30</td></tr> <tr><td>5</td><td>1</td><td>1</td><td>7.87</td><td>7.87</td></tr> </tbody> </table>	h(m)	Max	Med	D(m)	D(m)	1	33	20	1.57	1.57	2	8	5	3.15	3.15	3	4	2	4.72	4.72	4	2	1	6.30	6.30	5	1	1	7.87	7.87
	h(m)	Max	Med	D(m)	D(m)																																				
1	33	20	1.57	1.57																																					
2	8	5	3.15	3.15																																					
3	4	2	4.72	4.72																																					
4	2	1	6.30	6.30																																					
5	1	1	7.87	7.87																																					
Electronic	86.41.31.3	■	1	1,2W	5400	100	70°	Im = 64.00 Imax = 615.80 cd/klm F UTE 0.80 A Eta = 80.10% G=0.0° Alpha=38.2°+38.2° Beta=38.2°+38.2°																																	
LED	Electrónico	86.01.32.3	■	1	1,2W	4200	2227	10°	8641333 Semiplanos C		<table border="1"> <thead> <tr> <th>h(m)</th> <th>Max</th> <th>Med</th> <th>D(m)</th> <th>D(m)</th> </tr> </thead> <tbody> <tr><td>1</td><td>651</td><td>403</td><td>0.19</td><td>0.20</td></tr> <tr><td>2</td><td>163</td><td>101</td><td>0.37</td><td>0.40</td></tr> <tr><td>3</td><td>72</td><td>45</td><td>0.56</td><td>0.61</td></tr> <tr><td>4</td><td>41</td><td>25</td><td>0.74</td><td>0.81</td></tr> <tr><td>5</td><td>26</td><td>16</td><td>0.93</td><td>1.01</td></tr> </tbody> </table>	h(m)	Max	Med	D(m)	D(m)	1	651	403	0.19	0.20	2	163	101	0.37	0.40	3	72	45	0.56	0.61	4	41	25	0.74	0.81	5	26	16	0.93	1.01
	h(m)	Max	Med	D(m)	D(m)																																				
1	651	403	0.19	0.20																																					
2	163	101	0.37	0.40																																					
3	72	45	0.56	0.61																																					
4	41	25	0.74	0.81																																					
5	26	16	0.93	1.01																																					
Electronic	86.01.33.3	■	1	1,2W	5400	2227	10°	Im = 64.00 Imax = 10180.00 cd/klm F UTE 0.98 A + 0.02 T Eta = 100.00% G=0.0° Alpha=5.7°+5.0° Beta=5.3°+6.2°																																	
LED	Electrónico	86.01.34.3	■	1	1,2W	4200	340	24°	8641353 Semiplanos C		<table border="1"> <thead> <tr> <th>h(m)</th> <th>Max</th> <th>Med</th> <th>D(m)</th> <th>D(m)</th> </tr> </thead> <tbody> <tr><td>1</td><td>213</td><td>127</td><td>0.43</td><td>0.43</td></tr> <tr><td>2</td><td>53</td><td>32</td><td>0.85</td><td>0.85</td></tr> <tr><td>3</td><td>24</td><td>14</td><td>1.28</td><td>1.28</td></tr> <tr><td>4</td><td>13</td><td>8</td><td>1.70</td><td>1.70</td></tr> <tr><td>5</td><td>9</td><td>5</td><td>2.13</td><td>2.13</td></tr> </tbody> </table>	h(m)	Max	Med	D(m)	D(m)	1	213	127	0.43	0.43	2	53	32	0.85	0.85	3	24	14	1.28	1.28	4	13	8	1.70	1.70	5	9	5	2.13	2.13
	h(m)	Max	Med	D(m)	D(m)																																				
1	213	127	0.43	0.43																																					
2	53	32	0.85	0.85																																					
3	24	14	1.28	1.28																																					
4	13	8	1.70	1.70																																					
5	9	5	2.13	2.13																																					
Electronic	86.01.35.3	■	1	1,2W	5400	340	24°	Im = 64.00 Imax = 3331.00 cd/klm F UTE Inclasificable Eta = 75.66% G=0.0° Alpha=12.0°+12.0° Beta=12.0°+12.0°																																	
LED	Electrónico	86.01.36.3	■	1	1,2W	4200	210	14° x 40°	8641373 Semiplanos C		<table border="1"> <thead> <tr> <th>h(m)</th> <th>Max</th> <th>Med</th> <th>D(m)</th> <th>D(m)</th> </tr> </thead> <tbody> <tr><td>1</td><td>129</td><td>85</td><td>0.83</td><td>0.28</td></tr> <tr><td>2</td><td>32</td><td>21</td><td>1.66</td><td>0.56</td></tr> <tr><td>3</td><td>14</td><td>9</td><td>2.49</td><td>0.84</td></tr> <tr><td>4</td><td>8</td><td>5</td><td>3.32</td><td>1.11</td></tr> <tr><td>5</td><td>5</td><td>3</td><td>4.15</td><td>1.39</td></tr> </tbody> </table>	h(m)	Max	Med	D(m)	D(m)	1	129	85	0.83	0.28	2	32	21	1.66	0.56	3	14	9	2.49	0.84	4	8	5	3.32	1.11	5	5	3	4.15	1.39
	h(m)	Max	Med	D(m)	D(m)																																				
1	129	85	0.83	0.28																																					
2	32	21	1.66	0.56																																					
3	14	9	2.49	0.84																																					
4	8	5	3.32	1.11																																					
5	5	3	4.15	1.39																																					
Electronic	86.01.37.3	■	1	1,2W	5400	210	14° x 40°	Im = 64.00 Imax = 2011.00 cd/klm F UTE Inclasificable Eta = 71.37% G=0.0° Alpha=22.6°+22.6° Beta=7.9°+7.9°																																	